

MICROSOFT TEAMS ROOMS BAR



SPECIFICATIONS

PACKAGE INCLUDES

- Microsoft Teams Rooms Bar
- Cable bundle
- Monitor clamp
- Privacy cover

VIDEO INPUT

- 1x HDMI

VIDEO OUT

- 1x HDMI
- Touch display compatible

PEOPLE VIDEO RESOLUTION

- Supports maximum Zoom people resolution of 1080p @ 30fps (requires 1.8 Mbps)

CONTENT VIDEO RESOLUTION

- Supports maximum Zoom content sharing resolution of 1080p @ 15 fps

CONTENT SHARING

- HDMI Input
- Zoom Wireless Screen Sharing

CAMERA

- 5x digital zoom
- 120° FOV
- UHD 2160p (4K) capture resolution
- Automatic people framing
- Automatic speaker tracking

SPECIFICATIONS

ENVIRONMENTAL SPECIFICATION

- Operating temperature
 - 0 to 40 °C
- Operating humidity (non-condensing)
 - 15 to 80%
- Non-operating temperature
 - -40 to 70 °C
- Non-operating humidity (non-condensing)
 - 5 to 95%
- Maximum altitude
 - 16,000 ft

AUDIO INPUT

- 4x MEMS microphones
- Microphone pickup range up to 15 ft

AUDIO OUTPUT

- Single speaker

OTHER INTERFACES

- 1x USB-A (3.0)
- 1x USB-C

AUDIO STANDARDS AND PROTOCOLS

- Opus
- SILK
- G.722

NETWORK

- IPv4
- IPv6
- 1x 10/100/1G Ethernet
- Auto-MDIX
- Web proxy support
 - Basic
 - Digest
 - NTLM
- Simple Certificate Enrollment Protocol (SCEP)

PHYSICAL CHARACTERISTICS

- 17.39 W x 2.46 H x 2.42 D (inches)
441.8 W x 62.5 H x 61.6 D (mm)
- 1.6 lbs/.73 kg

SECURITY

- Authenticated access to admin menus, web interface, and API
- Local account password policy configuration
- Security profiles
- Local account and login port lockout
- Secure defaults
- Remote logging with support for TLS

OPTIONS SOLD SEPARATELY

- VESA and wall mount kit
- Stand
- TC8 touchpanel

INTEROPERABILITY

- Zoom Certified
- USB device mode

ELECTRICAL

- Auto sensing power supply
- Typical operating voltage/power
 - 37 VA @ 120 V @ 60 Hz
 - 37 VA @ 230 V @ 50/60 Hz
- Typical BTU/h
 - 65

LIMITED WARRANTY

- One year Limited Warranty

*Supported in future software update.